



1300
FFP3 NR D



CE EN 149:2001+ A1:2009

Foldable Series

1300 FFP3 NR D

- * 50 xOEL protection level (According to NPF)
- * Foldable
- * CE Certified
- * Complies with EN 149:2001+A1:2009 standards.

Suitable Application Areas

Pharmaceutical Industry / Ceramics / Food / Asbestos / Hospital Laboratory / Virus / Chemicals

Details




Read the Operating Instructions.



Storage Temperature Range




Shelf Life



Storage Humidity



Disposable



Provides requirements against clogging with Dolomite Powder



Foldable Series

1310 FFP3 V NR D

- * 50 xOEL protection level (According to NPF)
- * Foldable
- * Valve
- * CE Certified
- * Complies with EN 149:2001+A1:2009 standards.

Suitable Application Areas

Pharmaceutical Industry / Ceramics / Food / Asbestos / Hospital Laboratory / Virus / Chemicals

Details

CE EN 149:2001+A1:2009



Read the Operating Instructions.



Storage Temperature Range




Shelf Life



Storage Humidity



Disposable



Provides requirements against clogging with Dolomite Powder



4310
FFP3 V NR D



EN 149:2001+ A1:2009

Foldable C Series 4310 FFP3 V NR D

- * 50 xOEL protection level (According to NPF)
- * Foldable
- * Valve
- * CE Certified
- * Complies with EN 149:2001+A1:2009 standards.

Suitable Application Areas

Construction / Shipbuilding / Pharmaceutical Industry / Rubber Plastics / Engineering / Iron Steel / Agrochemicals / Laboratories / Agriculture / Base Metal Production / Lightweight / Coal Mining

Details



Read the Operating Instructions.



Storage Temperature Range




Shelf Life



Storage Humidity



Disposable



Provides requirements against clogging with Dolomite Powder



1200
FFP2 NR



CE EN 149:2001+A1:2009

Foldable Series

1200 FFP2 NR

- * 12 xOEL protection level (According to NPF)
- * Foldable
- * CE Certified
- * Complies with EN 149:2001+A1:2009 standards.


Suitable Application Areas

Construction / Shipbuilding / Pharmaceutical Industry / Rubber Plastics / Engineering / Iron Steel / Agrochemicals / Laboratories / Agriculture / Base Metal Production / Lightweight / Coal Mining

Details



Read the Operating Instructions.



Storage Temperature Range



Shelf Life



Storage Humidity



Disposable



6210
FFP2 V NR D



CE EN 149:2001+ A1:2009

Conical Series

6210 FFP2 V NR D

- * 12 xOEL protection level (According to NPF)
- * 0.6 mbar breath resistance
- * Valve
- * CE Certified
- * Complies with EN 149:2001+A1:2009 standards.

Suitable Application Areas

Construction / Shipbuilding / Pharmaceutical Industry / Rubber Plastics / Engineering / Iron Steel / Agrochemicals / Laboratories / Agriculture / Base Metal Production / Lightweight / Coal Mining

Details



Read the Operating Instructions.



Storage Temperature Range




Shelf Life



Storage Humidity



Disposable



Provides requirements against clogging with Dolomite Powder



4210
FFP2 V NR D



CE EN 149:2001+A1:2009

Foldable C Series 4210 FFP2 V NR D

- * 12 xOEL protection level (According to NPF)
- * Foldable
- * Valve
- * CE Certified
- * Complies with EN 149:2001+A1:2009 standards.

Suitable Application Areas

Construction / Shipbuilding / Pharmaceutical Industry / Rubber Plastics / Engineering / Iron Steel / Agrochemicals / Laboratories / Agriculture / Base Metal Production / Lightweight / Coal Mining

Details



Read the Operating Instructions.



Storage Temperature Range




Shelf Life



Storage Humidity



Disposable



Provides requirements against clogging with Dolomite Powder



7210
FFP2 V NR D



■ Activated Carbon Series

7210 ACTIVED CARBON FFP2 V NR D

- * 12 xOEL protection level (According to NPF)
- * Conical
- * Valve
- * CE Certified
- * Complies with EN 149:2001+A1:2009 standards.

Suitable Application Areas

Welding Smoke / Chemicals / Metal Fumes / Low Density Gases / Industrial Waste / Paint Vapors / Domestic Waste / Heavy Dust / Foundry

Details

- * Activated Carbon Filter provides excellent protection for welding fumes, solvent based vapors and heavy odors.

CE EN 149:2001+A1:2009



Read the Operating Instructions.



Storage Temperature Range




Shelf Life



Storage Humidity



Disposable



Provides requirements against clogging with Dolomite Powder

A faint, stylized lion head logo is centered in the background, facing left. It has a detailed mane and a calm expression.

FFP2-FFP3 MASK

GLOBAL SOLUTIONS

HEALTH&SAFETY

A large black L-shaped graphic is positioned in the corners of the slide. One L-shape is in the top-left corner, and another is in the bottom-right corner, framing the central content.



GLOBAL SOLUTIONS

HEALTH&SAFETY